Technical Specifications

HP E24i G4 WUXGA Monitor




OSD Buttons

Front

2. Power Button

Technical Specifications

HP E24i G4 WUXGA Monitor



- 1. Power Connector
- 2. DisplayPort™
- 3. HDMI Port
- 4. VGA Port

Back

- 5. USB-B Port
- 6. USB-A Ports (2)
- 7. USB-A Ports (2)

Technical Specifications

Models: 9VJ40AA

Panel SpecificationsDisplay Size (Diagonal)24-inDisplay Panel TypeIPS

Micro-Edge BezelYes, 3-sidedNative Resolution/Timing1920 x 1200 @60HzPanel Bit Depth8bit (6bit + FRC)

Aspect Ratio 16:10
Brightness - Typical 250 cd/m²
Static Contrast Ratio - Typical 1000:1
Static Contrast Ratio - Minimum 700:1
Dynamic Contrast Ratio (DCR) 5M:1
Flicker Free Yes

Pixel Pitch 0.2745 (H) × 0.2745(V)

Pixels Per Inch (PPI) 94

Backlight Lamp Life (to half brightness 30k minimum

- in hours)

Anti-Glare Panel Yes

Response Time - Typical 5ms GtG (with overdrive)

Horizontal Viewing Angle (typical 178°

CR>10)

Vertical Viewing Angle (typical CR>10) 178°

Panel Active Area (w x h) 527.04(H) × 296.46(V) mm

Preset Graphic Modes/Supported 640 × 480 @60Hz **Resolutions** 720 × 400 @70Hz

800 × 600 @60Hz 1024 × 768 @60Hz 1280 × 720 @60Hz 1280 × 800 @60 HZ 1280 × 1024@60Hz 1440 × 900 @60Hz 1600 × 900 @60Hz 1680 × 1050 @60Hz

Maximum Resolution 1920 × 1200 @60Hz Recommended Resolution 1920 × 1200 @60Hz

Vertical Scan Range50-60HzHorizontal Scan Range30-80kHzDefault Color TemperatureNeutral (6500K)Maximum Pixel Clock Speed170MHz

NOTE: Performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

Color Gamut Coverage sRGB 99%

Color Management Color Space / Subsampling Support RGB 4:4:4, YCBCR 4:4:4, YCBCR 4:2:2

Default Color Temperature Neutral (6500 K)

Low Blue Light Modes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution

certified)

RGB Channel Adjust Yes

Factory Color Calibrated Yes (Color Temperature)

Factory Color Presets Warm - 5000K,
Neutral - 6500K,
Cool - 9300K

Technical Specifications

Monitor Specifications Exterior Color of Monitor Bezel and Black head, Silver stand

Stand
Plug & Play
Yes

Tilt -5° to +23°
Swivel +/-45°
Pivot +/-90°
Height Adjustment Range 150mm

VESA Mounting 100mm x 100mm

Security Lock Ready Yes

Detachable Base Yes, ships detached **Warranty** Based on region

On Screen Display (OSD)

Specifications

Power & Operating

Specs

On Screen Display User Controls Brightness+, Color, Image, Input, Power, Menu,

Management, Information

Monitor Control Buttons or Switches Menu, Minus ("-")/Information, Plus ("+") / Viewing Mode,

OK/Next Active Input, Power

User-Assignable Function Buttons Yes, 3 (6 Options)

Languages 10 (German, Dutch, T-Chinese and S-Chinese, English,

Spanish, French, Italian, Japanese, Portuguese)

Connector Types DisplayPort™ 1.2 in

HDMI 1 HDMI1.4

VGA

HDCP support Yes, (DisplayPort™ and HDMI)

USB Port USB Version 3.2

USB Hub Yes
Nownstream Ports 4 Por

Downstream Ports4 PortsUpstream Ports1 Port

Fast Charging USB Ports 1 Port (Side) (USB-A) **Power Output Maximum** Fast Charging: 7.5 W

Special Features User Presets Yes

User Updateable Firmware Yes
Power Supply Internal

Power Source 100 – 240 VAC 50/60 Hz

Power Consumption - Maximum53 WEnergy Saving/Standby Mode0.5 WPower Consumption - Typical36 WPower cable length1.9 m

EU Energy Efficiency On-mode Power Consumption 16 W Class (ERP lot-5)

Annual Power Consumption 24 kWh
Energy Efficiency Class D

Visible Screen Size 24" / 60.69 cm Diagonal

Operating ConditionsOperating Temperature - Celsius $5^{\circ}-35^{\circ}C$ Operating Temperature - Fahrenheit $41^{\circ}C-95^{\circ}F$ Non-operating Temperature - Celsius $-34^{\circ}-60^{\circ}C$

Non-operating Temperature - Celsius $-34^{\circ}-60^{\circ}$ C Non-operating Temperature - $-29^{\circ}-140^{\circ}$ F

Fahrenheit

Technical Specifications

Operating Humidity 20 – 80% Relative Humidity (non-condensing) **Non-operating Humidity** 5 – 95%

Operating Altitude 0 – 5,000 m (16,400 ft.) **Non-operating Altitude** 0 – 12,192 m (40,000 ft.)

Environmental Features and Certifications

Mercury-free LED display backlighting

Arsenic-Free Display Glass

Low Halogen*

Yes, Mercury-free LED backlighting Yes

Yes

GSE HP-00011-01B, table 2 defines low-halogen (BFR, CFR,

PVC)

Agency Approvals and Certifications WW application

CE, CB, KC/KCC/NOM/ISO 9241-307/ EAC/TUV-GS/cTUVus/PSB/CCC/CEL/ISC/VCCI/FCC/BSMI/Vietnam MEPS/Australian-New Zealand MEPS/WEEE/BIS/CEC/E-

Standby/Low Blue Light/CECP/TUV-S/CECP

Microsoft WHQL Certification Win 11, Win 10, Win 8, Win 7 ENERGY STAR® Yes, ENERGY STAR® 8

EPEAT® Registered* Yes
TCO Certified Yes
China Energy Label CEL

CEL Grade 1
SmartWay Transport Partnership - NA
Yes (NA SKU)

only

NOTE: DisplayPort[™] and the DisplayPort[™] logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries.

Contains Recycled Plastics	85% recycled content by total weight
----------------------------	--------------------------------------

Unit Product/Package
Specifications

	<u>Metric</u>	<u>Imperial</u>
Product Dimensions (Unpacked with stand) (W x D x H)	53.2 x 20.69 x 50.96 cm	20.94 x 8.15 x 20.06 in
Product Dimensions (Packed) (W x D x H)	60.5 x 42 x 22.4 cm	23.82 x 16.54 x 8.82 in
Display Head Dimensions (Unpacked without stand) (W x D x H)	53.2 x 4.7 x 35.27 cm	20.94 x 1.85 x 13.88 in
Base Area Footprint (w x d mm)	260 x 207 mm	10.23 x 8.15 in
Bezel Measurements	Bottom 20.73 mm (display chin)	Bottom 8.16 in (display chin)
Product Weight (Unpacked with stand)	6.06 kg	13.36 lb
Product Weight (Packed)	9.12 kg	20.1 lb
Product Weight (Head Only)	3.6 kg	7.94 lb
Pallet Dimensions (L x W x H)	1220 x 1140 x2243 mm	48.03 x 44.88 x 88.31in
Pallet Total Weight (L x W x H)	40" GQ: 384 kg 40" HQ: 476 kg	40" GQ: 847 lbs 40" HQ: 1050 lbs
Pallet Layers	GQ: 4 HQ: 5	
Pallet Product per Layer	8	
Total Products per Pallet	GQ: 32	

GQ: 32 HO: 40

Pallet Information

^{*}External power supplies, power cords, cables and peripherals are not Low Halogen. Service parts obtained after purchase may not be Low Halogen.

Technical Specifications

Container Load, 20-Foot	460
Container Load, 40-Foot	960
Container Load, 40-Foot HighQ	960

Software Included HP Display Center

What's in the box? 1 HDMI (1.8 m) 5.9 ft 1 DisplayPort™ (DisplayPort™ 1.2) (1.8 m) 5.9 ft

1 USB-A-B cable (1.8 m) 5.9 ft 1 Power Cord (1.9 m) 6.2 ft

1 QSP 1 Doc-Kit

User Guide and Warranty Languages **User Guide Languages** English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.

Warranty Languages English, Arabic, S. Chinese, T. Chinese, Czech, Danish,

Dutch, Finnish, French, German, Greek, Hungarian, Italian, Japanese, Kazakh, Korean, Norwegian, Polish, Brazilian Portuguese, Russian, Slovenian, Spanish, Swedish and

Turkish.



Technical Specifications

Copyright © 2022 HP Development Company, L.P.

The information contained herein is subject to change without notice. The only warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency.



Summary

Change Log				
January 3, 2021	V1 to V2		Techspecs updated	
February 28, 2021	V2 to V3		Energy Efficiency Class Updated	
April 9, 2021	V3 to V4		Power Consumption updated	
April 13, 2021	V4 to V5	Update	VESA Mounting Specs	
May 26, 2022	V5 to V6	Update	Color Gamut Coverage specs	
June 28, 2022	V6 to V7	Update	Agency Approvals and Certifications	
April 13, 2023	V7 to V8	Updated	Color Management section	
December 20, 2023	V8 to V9	Added	Windows 11	
	V9 to V10			

